



DATA SHEET

Cyberware. Upgraded.

FireCuda 520 SSD Cyberpunk 2077 Limited Edition

Embrace the glow of Night City with the FireCuda[®] 520 Cyberpunk 2077 Limited Edition SSD. This NVMe PCIe[®] Gen4 SSD is encased in a custom designed Cyberpunk 2077 heatsink and features built in RGB LED lighting that makes your rig feel like it was ripped from the game. Plus, with only 2,077 drives being created—it's truly a limited edition.





Best-Fit Applications

- Creative professional systems
- High-performance PCs and workstations



Key Advantages

Designed with the officially licensed vibe of Cyberpunk 2077, this SSD is the perfect collectible for fans of the game.

Secure one of only 2,077 collectible SSDs being created.

Light up your rig with built in Cyberpunk 2077 LEDs featuring customizable RGB.

Our fast PCle Gen4 NVMe SSD features speeds up to 9x faster than SATA SSDs.

Leverage sequential read/write performance up to 5000/4400MB/s, and random read/write up to 760K/700K IOPS.

Heatsink technology helps your SSD maintain peak performance for longer periods of time.

Heatsink cooling effect lowers SSD temperature by up to 22 °C (71 °F).

Built to play a long time thanks to up to 0.7 DWPD, 1.8M MTBF, and 2800 TBW.

Enjoy peace of mind with our industry leading 5-year warranty and 3-years of Rescue Data Recovery Service ¹

Intended for desktop PCs. Heatsink is pre-installed and should not be removed as it can damage the device. Exceeds standard M.2 size specifications without a heatsink. The max dimensions of the FireCuda 520 with Cyberpunk 2077 heatsink are 80.15mm (L) x 22.9mm (W) x 18.25mm (H). Please verify that your system provides enough space for installation. SSD with heatsink is recommended for M.2 connectors H3.2 and above. Motherboard with 5V addressable header required for LED control.





| Specifications | 1TB | | |
|--|------------------------|--|--|
| Standard Model (TCG Pyrite) | ZP1000GM30012 | | |
| Interface | PCIe Gen4 ×4, NVMe 1.3 | | |
| NAND Flash Memory | 3D TLC | | |
| Form Factor | M.2 2280 | | |
| Performance | | | |
| Sequential Read (Max, MB/s), 128KB ¹ | 5000 | | |
| Sequential Write (Max, MB/s), 128KB ¹ | 4400 | | |
| Random Read (Max, IOPS), 4KB QD32 T8 ¹ | 760,000 | | |
| Random Write (Max, IOPS), 4KB QD32 T8 ¹ | 700,000 | | |
| Endurance/Reliability | | | |
| Total Bytes Written (TB) | 1800 | | |
| Mean Time Between Failures (MTBF, hours) | 1,800,000 | | |
| Rescue Data Recovery Services (years) ² | 3 | | |
| Warranty, Limited (years) | 5 | | |
| Power Management | | | |
| Active Power, Average (W) | 5.6 | | |
| Idle Power PS3, Average (mW) | 15 | | |
| Low Power L1.2 mode (mW) | 2 | | |
| Environmental | | | |
| Temperature, Operating Internal (°C) | 0 to 70 | | |
| Temperature, Nonoperating (°C) | -40°C – 85°C | | |
| Shock, Nonoperating: 0.5ms (Gs) | 1500 | | |
| Special Features | | | |
| TRIM | Yes | | |
| S.M.A.R.T. | Yes | | |
| Halogen Free | Yes | | |
| RoHS Compliance | Yes | | |
| Physical | | | |
| Length (mm/in, max) | 80.15mm/3.156in | | |
| Width (mm/in, max) | 22.86mm/0.90in | | |
| Height (mm/in, max) | 18.25mm/0.719in | | |
| Weight (g/lb) | 47g/0.104lb | | |

¹ Fresh out of box (FOB) performance obtained on newly formatted drive. Performance may vary based on SSD's firmware version, system hardware, and configuration. Performance based on CrystalDiskMark v.6.0.2 x64 on Windows 10 host with PCIe Gen4 motherboard.

² Rescue Data Recovery Services not available in all countries.





| Specifications | | | | | | | | |
|---------------------------|--------------------|----------------|--------------------------|-------------------|--|--|--|--|
| Retail Packaging | Product Dimensions | Box Dimensions | Master Carton Dimensions | Pallet Dimensions | | | | |
| Length (in/mm) | _ | 1.85in/47mm | 11.417in/290mm | 47.992in/1219mm | | | | |
| Width (in/mm) | _ | 4.252in/108mm | 12.441in/316mm | 40in/1016mm | | | | |
| Depth (in/mm) | _ | 5.276in/134mm | 6.654in/169mm | 45.984in/1168mm | | | | |
| Weight (lb/kg) | _ | 0.419lb/0.19kg | 5.732lb/2.6kg | 436.074lb/197.8kg | | | | |
| Quantities | | | | | | | | |
| Boxes per Master Carton | 10 | | | | | | | |
| Master Cartons per Pallet | 72 | | | · | | | | |
| Pallet Layers | 6 | | | | | | | |

System Requirements

- M.2 (M key) slot, PCle® G4 ×4 interface (backwards compatible with PCle G3 interface)
- Windows® 10
- Motherboard with 5V addressable header (for RGB LED light functionality)

What's Included

- Seagate[®] FireCuda[®] 520 Cyberpunk 2077 Limited Edition SSD
- RGB LED connector cable 46cm
- Quick start guide

| Region | Model Number | Capacity | Limited Warranty (years) | UPC Code | EAN Code | Multi-Pack UPC |
|--------|---------------|----------|-----------------------------|--------------|---------------|----------------|
| WW | ZP1000GM3A012 | 1TB | 5 | 763649161685 | 8719706420365 | 10763649161682 |

seagate.com



© 2021 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. FireCuda, the FireCuda logo, and SeaTools are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The NVMe word mark and/or NVMExpress design mark are trademarks of NVMExpress, Inc. The PCIe word mark and/or PCIExpress design mark are registered trademarks and/or service marks of PCI-SIG. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one teraphyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and drive capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS2070.1-2104US April 2021