

Savvio® 10K.6

Data Sheet

Enterprise Performance 10K HDD—The Perfect Performance Upgrade

- Transition from slower 2.5-inch, 10K-RPM or lower-capacity 3.5-inch, 15K-RPM hard drives to smaller, faster, best-in-class Savvio 10K.6 enterprise hard drives.
- PowerChoice™ technology for T10-compliant power management enables IT organizations to tailor systems for performance and power consumption.
- First mission-critical HDD to offer the Seagate® RAID Rebuild™ technology option—making RAID recovery faster and safer.
- Protection Information (PI) protects against inadvertent data change.¹
- Self-Encrypting Drive (SED) models can be used as standard drives or as part of a more secure solution.
- Seagate Instant Secure Erase (ISE) technology makes it safe, fast, and easy to retire, repurpose and sell drives.
- High capacity and small footprint enables data centers to keep pace with data growth and optimize data center real estate.
- FIPS 140-2, Level 2 certified SED models—only from Seagate—make FIPS 140-2 compliance quick and easy for US and Canadian government agencies.^{2,3}
- Seagate Unified Storage architecture reduces complexity and costs by converging disparate interfaces, form factors and security standards.

Best-Fit Applications

- Mission-critical servers and external storage arrays
- Power- and space-constrained data centers
- Green IT and drive-retirement cost reduction initiatives
- Compliance or data security initiatives
- Migration from 3.5-inch drive systems to next-generation technology



¹ Protection Information (PI) feature requires PI-compliant host or controller support.

² Not all drives may be available in all countries. SED and SED FIPS 140-2 Validated drives may use TCG-compliant host or controller support.

³ FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/validation.html#05>

Specifications	900GB ^{1,2}	600GB ^{1,2}	450GB ^{1,2}	300GB ^{1,2}
SED Model Number	ST900MM0026	ST600MM0026	ST450MM0026	ST300MM0026
SED FIPS 140-2 Model Number	ST900MM0036 ³			
Interface	6Gb/s SAS	6Gb/s SAS	6Gb/s SAS	6Gb/s SAS
Capacity				
Formatted 512 Bytes/Sector (GB)	900	600	450	300
External Transfer Rate (MB/s)	600	600	600	600
Performance				
Spindle Speed (RPM)	10K	10K	10K	10K
Average Latency (ms)	2.9	2.9	2.9	2.9
Sustained Transfer Rate Outer to Inner Diameter (MB/s)	204 to 125	204 to 125	204 to 125	204 to 125
Cache, Multisegmented (MB)	64	64	64	64
Configuration/Reliability				
Disks	3	2	2	1
Heads	6	4	3	2
Nonrecoverable Read Errors per Bits Read	1 per 10E16	1 per 10E16	1 per 10E16	1 per 10E16
Annualized Failure Rate (AFR)	0.44%	0.44%	0.44%	0.44%
Power Management				
Typical Op (amps) +5V/+12V	0.41/0.49	0.41/0.44	0.40/0.43	0.41/0.40
Power Idle (watts)	3.9	3.4	3.4	3.0
Environmental				
Temperature, Operating (°C)	5 to 55	5 to 55	5 to 55	5 to 55
Temperature, Nonoperating (°C)	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock, Operating: 11ms (Gs)	40	40	40	40
Shock, Nonoperating: 2ms (Gs)	400	400	400	400
Acoustics Idle (bels—sound power)	3.0	3.0	3.0	3.0
Vibration, Operating: <500Hz (Gs)	0.5	0.5	0.5	0.5
Vibration, Nonoperating: <500Hz (Gs)	3.0	3.0	3.0	3.0
Physical				
Height (in/mm, max) ⁴	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00
Width (in/mm, max) ⁴	2.760/70.10	2.760/70.10	2.760/70.10	2.760/70.10
Depth (in/mm, max) ⁴	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45
Weight (lb/kg)	0.467/0.212	0.487/0.221	0.489/0.222	0.479/0.217
Carton Unit Quantity	30	30	30	30
Cartons per Pallet	50	50	50	50
Cartons per Layer	10	10	10	10
Warranty				
Limited Warranty (years)	5	5	5	5

1 One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

2 Not all drives may be available in all countries. SED and SED FIPS 140-2 validated drives may use TCG-compliant host or controller support.

3 FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/validation.html#05>

4 These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223 (SAS models).



www.seagate.com

AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2012 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. PowerChoice, RAID Rebuild, Savvio, Seagate Secure and the Unified Storage architecture logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of hardware or software containing encryption may be regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and controlled for import and use outside of the U.S. Seagate reserves the right to change, without notice, product offerings or specifications. DS1768.1-1210US, October 2012